#### **Features**

- Available in four useful sizes
- Choice of power rating
- Wide bandwidth for music reproduction
- Wide dispersion for speech intelligibility
- Simple output-level selection
- Easily flush-mounted in ceilings or bulkheads
- Dependable rota-clamp fixing system
- Blends in with virtually all interiors

### **Description**

The EasyFit range of Ceiling Speakers are lightweight, quick and easy to install, and are finished in unobtrusive white with an attractive metal grille. The EasyFit Ceiling Speaker offers a wide frequency range along with good sound dispersion ensuring quality music reproduction and excellent speech intelligibility.

There are six models available in the range:

- 1. 5W 4.5" Ceiling loudspeaker
- 2. 5W 5" Ceiling loudspeaker
- 3. 5W 5" Ceiling loudspeaker (brilliant white finish)
- 4. 10W 6.5" Ceiling loudspeaker
- 5. 15W 8" Ceiling loudspeaker
- 6. 30W 8" Ceiling loudspeaker

The range of speakers uses a single-piece, dual-cone loudspeaker. A 100V matching transformer is mounted directly on the rear of the frame.

Connections are made using a screw terminal block designed for loop-through wiring which can be connected with or without the series capacitor, making it compatible with legacy equipment and EWIS control systems that utilize line monitoring circuitry.

# **Specifications**

	EasyFit 5w 4"	EasyFit 5w 5"	EasyFit 10w 6.5"	EasyFit 15w 8"	EasyFit 30w 8"
Rated Power	5 Watts	5 Watts	10 Watts	15 Watts	30 Watts
Maximum Power	8 Watts	8 Watts	15 Watts	22 Watts	45 Watts
Power Taps (Watts)	5, 2.5, 1.25, 0.66	5, 2.5, 1, 0.5	10, 5, 2.5 & 1.25W	15,10,5,2.5,1.25W	30, 15, 7.5, 3.75W
	0.33W	0.33W			
Frequency Range (-10dB)	100Hz - 15kHz	50Hz - 17kHz	60Hz - 20kHz	50Hz - 17kHz	50Hz - 17kHz
Axial Sensitivity 1W/1m/1kHz	94dB SPL	90dB SPL	91dB SPL	93dB SPL	93dB SPL
Axial Sound Pressure Level at		97dB at 1m/1kHz	101dB at 1m/1kHz	105dB at 1m/1kHz	108dB at 1m/1kHz
rated power					
Opening Angle (-6db)	144°/93°at1kHz	170° at 1kHz	170° at 1kHz	165° at 1kHz	100° at 1kHz
	/4kHz				
Ceiling Cut out diameter	140mm	170mm	195mm	238mm	238mm
Overall Dimension	170mm x 110mm	202mm x 90mm	220mm x 115mm	273mm x 115mm	273mm x 115mm
Safety			acc to EN60065		



IN FIRE DETECTION AND ALARM SYSTEMS



# EasyFit Ceiling Speaker Range

#### **Item Numbers**

218-0041	Ceiling Speaker, EasyFit 5w 4" White
218-0042	Ceiling Speaker, EasyFit 5w 5" Brilliant White
218-0043	Ceiling Speaker, EasyFit 5w 5" White
218-0044	Ceiling Speaker, EasyFit 10w 6.5" White
218-0045	Ceiling Speaker, EasyFit 15w 8" White
218-0046	Ceiling Speaker, EasyFit 30w 8" White

ADVANCED WA

SYSTEMS